## **EUROPEAN PATENT OFFICE**

## Patent Abstracts of Japan

**PUBLICATION NUMBER** 

07187734

**PUBLICATION DATE** 

25-07-95

APPLICATION DATE

24-12-93

APPLICATION NUMBER

05327477

APPLICANT : SEKISUI CHEM CO LTD;

INVENTOR: NITTA KATSUZO;

INT.CL

C04B 12/04 C04B 7/24 C04B 7/32 C04B 28/26 //(C04B 28/26 , C04B 14:30 ,

C04B 14:06 , C04B 16:06 ), (C04B 28/26 , C04B 14:06 , C04B 16:06 )

TITLE

CURABLE INORGANIC COMPOSITION

ABSTRACT: PURPOSE: To obtain a curable inorganic composition capable of producing an inorganic

formed article having excellent strength and durability.

CONSTITUTION: This composition is composed of 100 pts.wt. of an inorganic powdery material comprising 0.5-80wt.% of one or more of aluminum based additives selected from the group consisting of alumina cement, yelumina, flame sprayed alumina and sodium meta-aluminate and 99.5-20wt.% of the flyash having activated surface and an average particle diameter of ≤5.0µm obtained by subjecting flyash to a pulverization treatment, 3-200 pts.wt. of an alkali-metal silicate and 3-200 pts.wt. of water.

COPYRIGHT: (C)1995,JPO

(C) WPI / DERWENT

DC - L02

FS - CPI

IC - C04B7/24; C04B7/32; C04B12/04; C04B28/26

MC - L02-C03 L02-C07

PA - (SEKI) SEKISUI CHEM IND COLTD

PN - JP7187734 A 19950725 DW199538 C04B12/04 005pp

PR - JP19930327477 19931224

XA - C1995-130302

XIC - C04B-007/24; C04B-007/32; C04B-012/04; C04B-028/26; (C04B-014/08 C04B-014/30 C04B-016/06 C04B-028/26); (C04B-014/06 C04B-016/06 C04B-028/26)

AB - J07187734 Inorganic compsn. contains Al system additives contg. one or more of alumina cement, gamma alumina, thermally sprayed alumina (in total) 0.5-80 wt. %, inorganic powder (by wt. rate) 100, which contains fly-ash 99.5-20 wt. % of average grain dia. less than 5.0 mum, with alkali metal silicate: 3-200 and water: 3-200.

- ADVANTAGE - Effective utilisation of fly-ash as industrial waste.

- (Dwg.0/0)

- C04B28/26 C04B14/06 C04B14/30 C04B16/06;

- C04B28/26 C04B14/06 C04B16/06

IW - HARDEN INORGANIC COMPOSITION CONTAIN ALUMINIUM SYSTEM ADDITIVE

ALUMINA CEMENT GAMMA ALUMINA THERMAL SPRAY ALUMINA INORGANIC POWDER CONTAIN FLY ASH ALKALI METAL SILICATE

IKW - HARDEN INORGANIC COMPOSITION CONTAIN ALUMINIUM SYSTEM ADDITIVE

CONTAIN ALUMINA CEMENT GAMMA ALUMINA THERMAL SPRAY ALUMINA INORGANIC POWDER CONTAIN FLY ASH ALKALI METAL SILICATE

NC - 001

OPD - 1993-12-24

ORD - 1995-07-25

PAW-(SEKI) SEKISUI CHEM IND CO LTD

TI - Hardenability inorganic compsn. contg. aluminium system additives contains alumina cement, gamma alumina and/or thermally sprayed alumina, inorganic powder which contains fly-ash and alkali metal silicate